



**B-I-N® PRIMER  
SHELLAC-BASED SEALER & STAIN BLOCKER**

**DESCRIPTION AND USES**

Zinsser® B-I-N® Shellac-Based Primer is a primer-sealer, stain blocker, bond coat recommended for almost all surfaces. It blocks grease spots, fire, smoke, water stains, ink, crayon, dark colours, knots and sap streak stains and seals odours resulting from water and fire damage. B-I-N Primer ensures adhesion to hard-to-stick surfaces while hiding stains of all kinds. Some stains may require two coats. B-I-N Primer is ideal for hard-to-reach areas such as corners or drawers. Use under any solvent-based or water-based aerosol or brush paint.

**PRIMING INTERIORS**

Use to prime painted drywall, plaster, glass, vinyl, PVC, ceramic tile, plastic, chair rungs, fibreglass, hardboard and spackled areas. Ideal for hard-to-paint object such as wicker louvers, arts and crafts and more.

**PRODUCTS**

SKU	Description
76218	Satin White (369 g)

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Surfaces should be clean, dry, sound and free of dust, dirt, grime, grease, oil, wax, wallpaper adhesive or any contamination that may interfere with adhesion. Remove loose paint, dirt and rust. Mask off nearby objects.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Apply only when air, material, and surface temperatures are between 21°C and 27°C in a well ventilated area and avoid high humidity. Shake can vigorously until the agitator ball inside the can rattles. Turn the can upside down and continue shaking for at least 30 seconds. Repeat shaking occasionally during use. If the ball does not rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Spray 25-30 cm from object with short 'dusting' strokes.

**DRY TIME**

At normal temperatures, B-I-N will dry to the touch in 15 minutes and can be recoated or topcoated after 30 minutes.

**CLEAN-UP**

Wipe off tip before storing. Clean up wet paint with mineral turps. Throw away empty can in garbage pickup. Do not burn or puncture the can, even when empty.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not insert any object into the stem.



## TECHNICAL DATA

### B-I-N® PRIMER SHELLAC-BASED SEALER & STAIN BLOCKER

#### PHYSICAL PROPERTIES

Physical Properties		PRIMER SHELLAC-BASED SEALER & STAIN BLOCKER
Resin Type		Shellac-Based
Pigment Type		Titanium Dioxide, Aluminum Silicate, Mica
Solvents		Acetone, Ethanol, N-Butanol
MIR		0.80 Max
Fill Weight		369 g
Recommended Dry Film Thickness (DFT) per Coat		37.5-62.5µ
Practical Coverage at Recommended DFT (assume 15% material loss)		0.9-1.1 m <sup>2</sup> /can depending on application method and surface porosity
Dry Times at 21-27°C and 50% Relative Humidity	Touch	15 minutes
	Recoat	30 minutes
Shelf Life		5 years
Flash Point		-104°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Australia  
Unit 12, 4 Southridge Street  
Eastern Creek, NSW 2766  
PH: 1 300 784 476  
www.rustoleum.com.au  
email: sales@rustoleum.com.au

HAYDN BRUSH CO. LTD.  
PO Box 4325  
Christchurch, New Zealand  
PH: 64-3 384 7770  
email: mail@haydn.co.nz

Form: GDH-1003  
Rev.: 121715