



RUST-OLEUM® 2X ULTRA COVER ULTRA MATT FINISH SPRAYS

DESCRIPTION AND USES

Rust-Oleum® 2X ULTRA COVER contains breakthrough technology that provides twice the coverage on wood, metal, most plastic, wicker and more when compared to other matching colours of Rust-Oleum general purpose paints. It covers surfaces with less spray passes, allowing projects to be completed faster and easier. Any-angle spray feature allows you to spray in any direction, even upside down. Comfort spray tip with wider finger pad reduces fatigue caused by continuous spraying. Fast drying.

TIP: Some plastics made of polyethylene such as plastic storage containers are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first. Not for use on galvanised metal.

PRODUCTS

SKU	DESCRIPTION (Aerosol)
357852	Matt Deep Teal
357853	Matt Red
357854	Matt Slate
357855	Matt White
357856	Matt Black

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent or other suitable cleaning method. Rinse thoroughly with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces to create a surface profile.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

PRODUCT APPLICATION (cont.)

PRIMING

Use of a Rust-Oleum 2X Ultra Cover Primer provides excellent adhesion and hiding and is especially recommended for bare wood and metal.

PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 10°C and 32°C and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 93°C. Do not apply to galvanised metal. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

PAINTING

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN**. Contact Rust-Oleum. Shake often during use. Hold can upright 25-40 cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. Do not use near open flame.

DRY & RECOAT TIMES

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour, and is fully dry in 24 hours. Apply a second coat or clear coat within 1 hour or after 48 hours. Apply the clear in 2-3 light coats a few minutes apart. **NOTE:** On plastic, maximum paint adhesion and durability is achieved in 5-7 days.

CLEAN-UP

Wipe off tip before storing. Clean-up wet paint with mineral turps. Throw away empty can in garbage pickup. Do not burn or puncture the can even when empty.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not insert a pin or other object into the stem.



**RUST-OLEUM® 2X ULTRA COVER
ULTRA MATT FINISH SPRAYS**

PHYSICAL PROPERTIES

		2X ULTRA COVER ULTRA MATTE SPRAYS
Resin Type		Modified Alkyd
Pigment Type		Varies by color
Solvents		Acetone, Naptha, Mineral Spirits, Xylene, N-butyl Acetate
MIR		Max 0.95
Fill Weight		12 oz.
Recommended Dry Film Thickness (DFT) per Coat		25-50µ 1.0-2.0 mils
Practical Coverage at Recommended DFT (assume 15% material loss)		0.56-0.93 m ² /can 6-10 sq.ft./can
Dry Times at 70F (21°C) and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	Within 1 hour or after 48 hours
Dry Heat Resistance		93°C (200°F)
Shelf Life		5 years
Flash Point		-104°C (-156°F)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.