



# RUST-OLEUM® MIRROR EFFECT

## DESCRIPTION AND USES

Rust-Oleum® Mirror Effect is an innovative coating that transforms glass and acrylic glass into a unique mirror finish. It is ideal for glass vases, candleholders, framed glass, jars and tabletops. **Apply to the reverse or opposite side of glass. Interior use only.**

It features a comfort tip with a wider finger pad to reduce fatigue caused by continuous spraying and the any-angle tip which allows you to spray at any angle.

## PRODUCT

SKU	DESCRIPTION (Aerosol)
347809	Mirror Effect

## PRODUCT APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Apply when temperature is between 10-32°C and humidity is below 85% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 93°C or galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

## SURFACE PREPARATION

Remove water spots and other imperfections on substrate to achieve optimal results. Clean glass thoroughly with glass cleaner or soap and water, using a lint free cloth. Allow glass to dry completely before painting. Coating will not hide imperfections on substrate.

## PRODUCT APPLICATION (cont.)

### APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN**. Contact Rust-Oleum. Make sure to apply paint to the reverse side of glass that will be displayed. Hold can upright 25-30 cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Apply using very thin coats, allowing the paint to dry for 1 minute between coats. Apply up to 5 coats to achieve the desired mirror effect. Paint will rapidly change in appearance and mirror effect will appear while coating dries. The painted side will appear dull with the reverse side showing the mirror finish. **Do not use near open flame.**

### DRY & RECOAT

Dry and recoat times are based on 21°C and 50% relative humidity. Dries completely in 5-10 minutes. May be recoated at any time. For added protection, apply a thin coat of Rust-Oleum Ultra Cover 2X Matte Clear to the painted side.

### CLEAN-UP

Wipe off tip before storing. Clean-up wet paint with xylene or mineral turps. Properly discard empty container. Do not burn or place in home trash compactor.

### CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not insert any object into can valve opening.

	<b>TECHNICAL DATA</b>	<b>SPC-80</b>
<b>RUST-OLEUM®</b> <b>MIRROR EFFECT</b>		

**PHYSICAL PROPERTIES**

		MIRROR EFFECT
<b>Resin Type</b>		Cellulose Ester
<b>Pigment Type</b>		NA
<b>Solvents</b>		Acetone, N-Butyl Acetate
<b>MIR</b>		1.35 Max
<b>Fill Weight</b>		170g
<b>Wet Film to Achieve (DFT)</b>		2-5 light wet coats
<b>Dry Times at 21-27°C and 50% Relative Humidity</b>	<b>Touch</b>	5-10 minutes
	<b>Recoat</b>	Anytime
	<b>Fully Dry</b>	5-10 minutes
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		-104°C
<b>Safety Information</b>		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.