



RUST-OLEUM® GLITTER SPRAYS

DESCRIPTION AND USES

Rust-Oleum® Glitter Sprays are designed to provide a sparkle finish on many surfaces including wood, metal, wicker, ceramic, pottery, Styrofoam®, paper, plastic, and more. For added protection, top coat with Rust-Oleum® Glitter Sealer. The clear topcoat helps prevent Glitter from flaking and fading while maintaining the sparkle finish. For use on interior items only.

PRODUCTS

SKU	DESCRIPTION (Aerosol)
347863	Glitter Gold
347864	Glitter Silver
347865	Glitter Clear

PRODUCT APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 10°C and 32°C and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 93°C. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces to create a surface profile.

PRODUCT APPLICATION (cont.)

PRIMING

Use of a Rust-Oleum primer provides superior adhesion and hiding and especially recommended for bare wood and metal. A primer, however, is not recommended for Styrofoam® and paper. The following primers are recommended.

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle, **DO NOT STRIKE CAN**. Contact Rust-Oleum. Shake often during use. Hold can upright 30-35cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart. **Do not use near open flame.**

DRY & RECOAT

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour, and fully dry in 24 hours. Recoat at anytime.

CLEAN-UP

When finished spraying, clear valve by turning can upside down and pushing spray button for 5 seconds. Clean-up wet paint with xylene or mineral turps. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not insert any object into can valve opening.

*Styrofoam® is a trademark of the Dow Chemical Company

	TECHNICAL DATA	SPC-81
RUST-OLEUM® GLITTER SPRAYS		

PHYSICAL PROPERTIES

Physical Properties		GLITTER SPRAYS
Resin Type		Acrylic
Pigment Type		Glitter Flake
MIR		0.95 Max
Fill Weight		219g
Solvents		Heptane, N-Butane, Propane, VM&P Naphtha
Dry Times at 25°C and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	Anytime
Shelf Life		5 years
Flash Point		-96°C
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.