



RUST-OLEUM® CHALKED MATT SPRAYS

DESCRIPTION AND USES

Rust-Oleum® Chalked Ultra Matt Sprays create an ultra matte finish with excellent coverage and adhesion on furniture and home décor. Chalked Ultra Matt Sprays provide one coat coverage on most surfaces without special surface preparation or priming. It can be painted or distressed, giving the project a one of a kind look. It is suitable for use on wood, metal, ceramic, glass, canvas and more.

Chalked Ultra Matt Sprays feature an advanced spray system that allows you to spray at any angle, even upside down for those hard to reach areas. A comfort spray tip with a wider finger pad to reduce fatigue caused by continuous spraying.

TIP: Some plastics made of polyethylene such as plastic storage containers are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first.

PRODUCTS

SKU	DESCRIPTION
320868	Charcoal
320870	Linen White
320881	Aged Grey
320882	Country Grey
320883	Blush Pink
320884	Serenity Blue
347788	Cocoa Bean
347789	Farmhouse Red
347790	Coastal Blue
347791	Tidal Pond
347792	Chiffon Cream
347793	Clear Topcoat

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with soap and water and let dry. Remove loose paint and rust with a wire brush or sandpaper. To enhance adhesion, lightly sand glossy or porous surfaces. Remove any wax by lightly wiping the surface with mineral turps.

PRIMING

Priming is not required for most surfaces. For excellent coverage, use of a Rust-Oleum primer can be used on surfaces such as treated wood, bare metal and treated wood. When applying a light colour over a dark surface, a primer is required to prevent tannin bleed.

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Apply when the temperature is between 10°C and 32°C and humidity is below 85% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover the surrounding area to protect from spray mist.

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 25-30 cm from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart. Do not use near open flame.

DRY & RECOAT

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 20 minutes and is dry to handle in 1 hour. May be recoated in 1 hour or after 48 hours. The finish coat is fully dry in 24 hours. NOTE: On plastic, maximum paint adhesion and durability is achieved in 5-7 days. Chalked Clear Protective Topcoat can be applied for added protection. Apply according to the label instructions.

CLEAN UP

Wipe off tip before storing. Clean-up wet paint with xylene or mineral turps. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral turps. Do not insert any object into can valve opening.

DISTRESSING

This paint can be distressed if desired. To distress the surface, lightly sand the surface with fine to medium grit sandpaper or a sanding sponge. Wait 2 hours before sanding or distressing.

	TECHNICAL DATA	CHD-12
<small>TRUSTED QUALITY SINCE 1921</small> RUST-OLEUM® <i>Chalked</i>	RUST-OLEUM® CHALKED MATT SPRAYS	

PHYSICAL PROPERTIES

		CHALKED ULTRA MATT SPRAYS
Resin Type		Acrylic Modified Alkyd
Pigment Type		Varies with color
Solvents		Acetone, Mineral Turps
MIR		0.80 Max
Fill Weight		340 g
Recommended Dry Film Thickness (DFT) per Coat		25-50µ (1.0-2.0 mils)
Practical Coverage at Recommended DFT (assume 15% material loss)		0.65-0.75 m ² /can (7-8 sq.ft./can)
Dry Times at 21-27°C and 50% Relative Humidity	Touch	30 minutes
	Handle	1 hour
	Recoat	Within 1 hour or after 48 hours
Shelf Life		5 years
Flash Point		-104°C (-156°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.